



Item# _____

Job _____



LINEN TRUCK CLT SERIES

- **Versatile Construction:** By positioning the two folding shelves on the CLT – either horizontally or vertically – three different truck configurations become possible:

- #1. Folding shelves can be positioned horizontally for easy transport and accessibility for fresh linen. (35-40-bed capacity)
- #2. Folding shelves can be positioned vertically to become an enclosure panel, creating a spacious rolling bin for the collection and the transportation of soiled linen.
- #3. While folding shelves are in a vertical position, the lower folding shelf can be flipped out and up, enabling contents to be unloaded with a minimum amount of handling.

Note: See illustrations on back.

- **Open Wire Features:** Minimize dust accumulation and allow a free circulation of air, greater visibility of stored items and greater light penetration.
- **Brake Lock/Swivel Lock Combination Casters:** Enable a single pair of casters to serve as swivel, rigid or brake casters to meet varying operational needs. See sheet #11.70.
- **Covers Available:** Catalog numbers on reverse side. See sheet #11.80.
- **Pitched Aluminum Dust Cover:** Shields lower truck contents against dust or dirt.
- **Cart-Washable**



Heavy-Duty

Heavy-duty models contain heavier gauge corner posts and two additional intermediate frames.



Standard-Duty



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com

Job _____



LINEN TRUCK CLT SERIES

DIMENSIONS

| Model No. | Description | Width | | Shelf Size Length | | Height | | |
|----------------------------------------|----------------------------|-------|------|-------------------|------|--------|------|--|
| | | (in.) | (mm) | (in.) | (mm) | (in.) | (mm) | |
| STANDARD-DUTY CHROME | | | | | | | | |
| CLTS2460C | CLT with 3-sided top frame | 24 | 610 | 60 | 1525 | 70 | 1775 | |
| CLTS2448C | CLT with 3-sided top frame | 24 | 610 | 48 | 1220 | 70 | 1775 | |
| STANDARD-DUTY - STAINLESS STEEL | | | | | | | | |
| CLT2460S | CLT with 3-sided top frame | 24 | 610 | 60 | 1525 | 70 | 1775 | |
| HEAVY-DUTY - CHROME | | | | | | | | |
| CLTH2460C | CLT with 3-sided top frame | 24 | 610 | 60 | 1525 | 70 | 1775 | |

Material: Chrome Models: chrome-plated steel dolly and aluminum tubes. Stainless Steel: stainless steel dolly and aluminum tubes.

Note 1: Casters on above units consist of two 6P and one pair BL6P, 8P and BL8P available on special order.

Note 2: Before employing any of various cart-washing systems, please contact InterMetro representative for special recommendations on casters and for cleaning instructions.

ACCESSORIES

UNCOATED COVERS

| Width | | Length | | Height | | Zippered Closure | Velcro Closure |
|-------|------|--------|------|--------|------|------------------|----------------|
| (in.) | (mm) | (in.) | (mm) | (in.) | (mm) | Cat. No. | Cat. No. |
| 24 | 610 | 48 | 1220 | 62 | 1575 | 24x48x62UC | 24x48x62VUC |
| 24 | 610 | 60 | 1520 | 62 | 1575 | 24x60x62UC | 24x60x62VUC |

COATED COVERS

| Width | | Length | | Height | | Zippered Closure | Velcro Closure |
|-------|------|--------|------|--------|------|------------------|----------------|
| (in.) | (mm) | (in.) | (mm) | (in.) | (mm) | Cat. No. | Cat. No. |
| 24 | 610 | 48 | 1220 | 62 | 1575 | 24x48x62C | 24x48x62VC |
| 24 | 610 | 60 | 1520 | 62 | 1575 | 24x60x62C | 24x60x62VC |

Manufactured by:



InterMetro Industries Corporation

North Washington Street, Wilkes-Barre, PA 18705

Phone: 570-825-2741 • Fax: 570-825-2852

For Product Information Call: 1-800-433-2232

Visit Our Web Site: www.metro.com

L02-159
Rev. 12/99
Printed in U.S.A.

Information and specifications are subject to change without notice. Please confirm at time of order.

