

SOLID SLIDE LID GLASS & PLATE CHILLER

Project Name:	
Project Location:	
Model #:	Quantity:
Available Warehouse:	

Model: EGC37 EGC Series



Refrigeration System

- Bottom mounted, self-contained and retractable condensing unit uses environmentally friendly, EPA compliant R290 refrigerant with zero (0) Ozone Depletion Potential (ODP) and three (3) Global Warming Potential (GWP). Blizzard R290 is easily replaceable and require no on-site brazing.
- Electronically commutated (ECM) fan motors achieve rapid cooling with less energy consumption.
- Full-length air duct system ensures optimal circulation of cold air.
- · Time-initiated and temperature-terminated defrost cycle with defrost heater.
- · Large capacity, corrosion-resistant condenser and evaporator coils.
- Large capacity, corrosion-resistant condenser and evaporator cons.
 Self-maintaining, energy-efficient condensate drain pan requires no external drains or electric heaters.
 High performance, auto-reverse condenser fan motor supports compressor ventilation and condenser coil cleaning. Refer to owner's manual for full maintenance instructions.
 Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P.

Cabinet Construction

- · Heavy duty stainless steel countertop and rails with textured laminate, black vinyl exterior.
- · Open spaced interior with no walls between compartments.
- Galvanized steel interior
- · 1 3/4" thick high density polyurethane insulation.
- Built-in caster thread receptacles for all models.

Lighting

· Shielded LED bar lighting with on/off switch provides bright, high color illumination at lower heat output.

- · Heavy duty stainless steel exterior and galvanized steel interior.
- · 3/4" thick high density polyurethane insulation.
- · Removable ratchet locks keep your items safe from theft.

· Two levels of epoxy coated, steel wire shelves slide horizontally for easy storage of glasses and plates (see table for quantity).

Temperature Control

- · Multi-function digital controller with easy to read LED display. Factory preset temperature, -4°F.
- \cdot Temperature setting range from -10°F to 54°F.
- Audible overheat protection alarm for compressor and condenser coil.

Options

- \cdot 3" or 5" swivel casters with locks.
- · 3.5" 6" height-adjustable and interchangeable legs.



















Please visit our website for updated Energy Efficiency information

Ref/	Lids	Сара	city	Shelves	Refrigerant	HP	Power	Amps	Crated	Exterior Dimensions		
Frz/Dual	Lido	Cu. Ft.	(8") Mugs	Cilcirco	Homigorant		V-Hz-Ph	Allipo	Weight	L	D	H*
FRZ	1	11	160	3	R-290	1/2	115-60-1	5	209 lbs (95kg)	36.75" (933mm)	26.75" (679mm)	33.75" (857mm)



SOLID SLIDE LID GLASS & PLATE CHILLER

EGC Series Model: EGC37

STORAGE DATA

Net Capacity Cu. Ft. ►	11
Shelves	3
Barrels	-
20 oz. Bottles	-
12 oz. Bottles	-
12 oz. Cans	-
8" Mugs	160
# of Pans (Top)	-
# of Pans (Drawer)	-
Dividers	-
Trays	-

ELECTRICAL DATA

Voltage	115-60-1
Full Load Amperage	5A
Feed Wires with Ground	3
Cord Length	9ft
NEMA Plug Type	○ NEMA 5-15P

REFRIGERATION DATA

Compressor Mounting	Side
Refrigerant	R-290
Compressor HP	1/2
BTU/HR [†]	1979


KEY

FD					
----	--	--	--	--	--


	Elevation	Right	Plan	3D	Back
KCL					


36 3/4" 32 1/8" 33 3/4"

PLAN VIEW



FRONT





SIDE

ACCESSORIES & OPTIONS

Part Number	Description
AJL03-00	Interchangeable Leg for Caster (Optional)
CASA3-01	3" Overall Height Caster Assembly - (2) Front (2) Rear
CASA5-01	5" Overall Height Caster Assembly - (2) Front (2) Rear