



Item # _____

We put space to work.

Job _____

MetroMax® 4 Polymer Mobile Shelving & Stem Caster Carts

All-polymer corrosion proof shelves & posts combined with stem casters offer a sturdy, long lasting movable storage solution or transport cart. Rigid one-piece shelf frame with wraparound corners provides complete 360° capture of the wedge and post to ensure stability and overall strength. Shelves have polymer shelf mats that are impact resistant for long life and quick-to-remove for easy routine cleaning. Shelves and polymer posts offer a lifetime warranty against rust and corrosion. Shelf mats and posts have built-in Microban® antimicrobial product protection. Each cart can safely store or transport up to 750 lbs (340kg) evenly distributed. Units assemble easily—shelves mount on four one-piece wedges along grooved, numbered posts. Shelves adjust on 1" (25mm) increments.

- **Easy ordering:** one part number includes the shelves, posts, casters, and bumpers for a full mobile unit.
 - Four-shelf models include (4) open grid mat shelves.
 - Five-shelf models include (1) solid bottom shelf and (4) open grid shelves.
- **Durability:** All-polymer shelves and posts are rust proof.
- **Polymer shelves and posts offer a Lifetime Warranty** against rust and corrosion.
- **5PCX/5PCBX** polymer casters are rust resistant for wet environments.
- **Proven Stability:** Proven Metro corner design and rigid four-sided shelf frame assure sturdy carts.
- **Easy-to-Clean:** 6" (152mm) wide shelf mats easily remove from the shelf for cleaning by hand or in a commercial washer / dish machine.
- **Microban® Antimicrobial Product Protection** is built into the shelf mats and posts to inhibit the growth of bacteria, mold, mildew, and fungus that cause odors and product degradation. Microban product protection keeps the product "cleaner between cleanings".
- **Protective Surfaces:** Smooth, flat surfaces protect packaged shelf contents from unwanted rips, tears, or damage.
- **Efficient Use of Space:** Shelves adjust on 1" (25mm) increments along the post to maximize the use of available vertical space.
- **Fast, Easy Assembly Shelves;** are ready to use right out of the box. One-piece wedges securely attach to the posts – Raised beads on the back of each wedge snap into the grooves on the post. Window on wedge aligns with numbers on the post to locate the desired shelf position. Shelf seats into position over the posts and wedges. A unit can be assembled without tools in minutes.
- **NSF Listed:** for all environments.
- **Optional Accessories:** are on spec sheet 9.25.



4-shelf model



5-shelf model w/ solid bottom



MetroMax® 4 Polymer Mobile Shelving / Stem Caster Carts



Supports good **HACCP** processes

MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban® Products Company, Huntersville, NC. Microban® product protection does not by itself protect a user from food borne illness. Product must be routinely cleaned.



InterMetro Industries Corporation
North Washington Street, Wilkes-Barre, PA 18705
Product Information. U.S. and Canada: 1.800.992.1776
Outside U.S. and Canada: www.metro.com/contactus

LO2-207 Printed in U.S.A. 6/22

Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2022 InterMetro Industries Corp.

9.15

MetroMax[®] 4 Polymer Mobile Shelving & Stem Caster Carts

Material Specifications:

- **Shelf Mats:** Polypropylene. Mats contain Microban[®] antimicrobial product protection.
- **Longitudinal beams:** Pultrusions — continuous glass fibers and thermoset resin composite.
- **End Beams, Adjustable Foot and Socket, Shelf Wedge Connector:** reinforced nylon.
- **Polymer Posts:** Pultrusions — continuous glass fibers and thermoset resin composite with built-in Microban[®] antimicrobial product protection.
- **Post Cap:** High-density polyethylene.
- **Continuous Temperature Exposure Range (with shelves under load):** -20/120° F (-29/49° C).
- **For cleaning** the maximum intermittent temperature exposure is 212° F (100° C).
- **Polymer casters (5PC/5PCBX):** Nylon horn, SS axle bolt, polyurethane caster tread, Stainless steel axle, zinc plated raceway. Bumpers are nonphthalate, flexible vinyl.

4-Tier Open Grid Mats

Unit Height 67.31 (1710mm)

Nominal Width/Length (in./mm)		Approx. Pkd. Wt. (lbs./kg)		Cat. No. 2-Swivel, 2-Brake Polyurethane Casters
18x36	457x914	50.6	22.9	X336PG4
18x48	457x1219	58.3	26.5	X356PG4
18x60	457x1524	66.6	30.2	X366PG4
24x36	610x914	57.2	25.9	X536PG4
24x48	610x1219	67.6	30.7	X556PG4
24x60	610x1524	77.2	35.0	X566PG4

5-Tier w/ Solid Bottom

Unit Height 79.31 (2015mm)

Approx. Pkd. Wt. (lbs./kg)		Cat. No. 2-Swivel, 2-Brake Polyurethane Casters
61.0	27.7	5X337PG4
70.7	32.1	5X357PG4
81.0	36.8	5X367PG4
69.3	31.4	5X537PG4
82.3	37.3	5X557PG4
94.3	42.8	5X567PG4



5PCX
Swivel caster



5PBCX
Swivel / Brake caster



MetroMax bumper
(included with casters)